

STANDARD FEATURES

- DURABLE STAINLESS STEEL TOP, INTERIOR WALLS, FLOOR AND CEILING.
- EXTERIOR CONSTRUCTION IS ATTRACTIVE CORROSION RESISTANT VINYL ON STEEL IN BLACK FINISH.
- REFRIGERATION SYSTEM KEEPS THE DRINKS AT SAFE TEMPERATURES BETWEEN 33°F AND 41°F (0.5°C TO 5°C).
- ELECTRONIC CONTROL SYSTEM MAKES IT EASY TO ADJUST TEMPERATURE SET POINT AND DEFROST FREQUENCY.
- OPTION OF STAINLESS STEEL EXTERIOR AVAILABLE.
- PREINSTALLED HEAVY-DUTY CASTERS WITH BRAKES. OPTION OF LEVELING FEET AVAILABLE.
- SHELVES: ADJUSTABLE HEAVY-DUTY PVC COATED SHELVES.
- SELF-CLOSING DOORS WITH LOCKS.
- LED INTERIOR LIGHTING.
- REMOVABLE INSTALLATION BOARD MAKES IT EASY TO ACCESS CONDENSER COIL FOR CLEANING AND SERVICE.
- REFRIGERANT: HYDRO-CARBON R290.



UBB-1F-HC



UBB-2F-HC



UBB-3F-HC



UBB-4F-HC



| MODEL | DOORS | CAPACIT | | SHELVES | AMPS | HP | VOLTAGE | NEMA PLUG | CABINET DIMENSIONS | | |
|-----------|-------|---------|--------|---------|------|------|----------|-----------|---------------------|---------------------|---------------------|
| | | CU.FT | LITERS | | | | | | L | D | H |
| UBB-1F-HC | 1 | 6.5 | 186 | 2 | 1.92 | 1/6 | 115/60/1 | 5-15P | 23 ^{1/2} " | 30 ^{3/8} " | 38 ^{3/4} " |
| UBB-1F-HC | 2 | 19 | 546 | 4 | 2.88 | 1/5 | 115/60/1 | 5-15P | 58 ^{7/8} " | 27 ^{3/4} " | 35 ^{5/8} " |
| UBB-1F-HC | 2 | 23.3 | 666 | 4 | 3.6 | 1/5 | 115/60/1 | 5-15P | 69 ^{1/8} " | 27 ^{3/4} " | 35 ^{5/8} " |
| UBB-1F-HC | 3 | 32 | 916 | 6 | 4.7 | 1/4+ | 115/60/1 | 5-15P | 90 ^{1/2} " | 27 ^{3/4} " | 35 ^{5/8} " |