

STANDARD FEATURES

- DURABLE STAINLESS STEEL TOP, INTERIOR WALLS, FLOOR AND CEILING.
- EXTERIOR CONSTRUCTION IS ATTRACTIVE CORROSION RESISTANT VINYL ON STEEL IN BLACK FINISH.
- REFRIGERATION SYSTEM KEEPS THE DRINKS AT SAFE TEMPERATURES BETWEEN 33°F AND 41°F (0.5°C TO 5°C).
- ELECTRONIC CONTROL SYSTEM MAKES IT EASY TO ADJUST TEMPERATURE SET POINT AND DEFROST FREQUENCY.
- OPTION OF STAINLESS STEEL EXTERIOR AVAILABLE.
- PREINSTALLED HEAVY-DUTY CASTERS WITH BRAKES. OPTION OF LEVELING FEET AVAILABLE.
- SHELVES: ADJUSTABLE HEAVY-DUTY PVC COATED SHELVES.
- SELF-CLOSING DOORS WITH LOCKS.
- LED INTERIOR LIGHTING.
- REMOVABLE INSTALLATION BOARD MAKES IT EASY TO ACCESS CONDENSER COIL FOR CLEANING AND SERVICE.
- REFRIGERANT: HYDRO-CARBON R290.

UDD-1-HC



UDD-2-HC



UDD-3-HC



UDD-4-HC



MODEL	DOORS	CAPACIT		SHELVES	AMPS	HP	VOLTAGE	NEMA PLUG	CABINET DIMENSIONS		
		CU.FT	BARRELS.						L	D	H
UBB-1G-HC	1	6.5	1*1/2	2	1.92	1/6	115/60/1	5-15P	23 ^{1/2} "	30 ^{3/8} "	38 ^{3/4} "
UBB-1G-HC	2	19	2*1/2	4	2.88	1/5	115/60/1	5-15P	58 ^{7/8} "	27 ^{3/4} "	35 ^{5/8} "
UBB-1G-HC	2	23.3	3*1/2	4	3.6	1/5	115/60/1	5-15P	69 ^{1/8} "	27 ^{3/4} "	35 ^{5/8} "
UBB-1G-HC	3	32	4*1/2	6	4.7	1/4+	115/60/1	5-15P	90 ^{1/2} "	27 ^{3/4} "	35 ^{5/8} "