

### PRINCIPAL APPLICATIONS

Designed for continuous operation in, chillers, coolers, vending and general water applications

### PIPES, FITTINGS AND MOUNTING PLATES

- SPC pumps are fitted to python systems to provide the optimum cooling rate for soft drinks, beers and wines
- Braided hose or brewery tubing complete with fittings available to order
- Alternative mounting plates in stainless steel available to order

### WETTED MATERIALS

- PP or stainless steel mounting plate
- Glass filled ABS Column & Pump Body with PP Impellers
- Stainless steel shaft
- Nylon Agitator

### FEATURES

- Up to 15.8 litres/minute, Up to 12.1 metres head
- Low maintenance and long life
- Available with plugs and leads to suit application
- Agitator propeller fitted as standard
- Top mounted with keyhole mounting plate
- IPX4 motor housing
- Two stage pump head



## Specification

Model	Weight	Lenght	Height	Run-out flow rate (l/min)	Closed valve head (m)	Output port (mm)	Temt range (degC)	*max specific gravity	Motor output (watts)
PV42	2.5 kg	319 mm	117 mm	50 Hz 14.2	12.1	Plain 11/12.5 combined	-20 to +85	1.0	60
				60 Hz 15.6	15.4				

\*Assuming maximum viscosity of 30cp.

### DIMENSIONS

Drawings not to scale Dimensions in millimetres

