



COMPACT REGULATOR

SECONDARY



DEDICATED TO
DRAFT QUALITY

COMPACT REGULATOR

SECONDARY

PRODUCT

- This new Compact secondary regulator is a light version of the previous Compact secondary regulator.
- The handle is identical to the handle on the existing model and set at maximum 3.1 bar.
- The capacity has been increased compared to the existing Compact secondary regulator.
- The inlet connections are flexible and both the right and the left side can be used for the inlet.
- If the Compact secondary is used only as single reducer it is sufficient to use the blind plug in the free JG connection.
- Tamper evident devices are available to fix the required setting.

SPECIFICATION

- Material:
 - body: PPO
 - bracket: POM
 - valve seat: POM
 - SOV: POM
- Inlet connections: 3/8" JG + 1 JG blind plug
- Outlet connection: SOV + 3/8" JG
- Capacity: 60 l/min maximum
- Weight: 120 g
- Dimensions: 120 x 80 x 85 mm
- Media: CO₂, N₂ and mixed gasses
- Max. inlet: 7 bar / 102 PSI
- Working pressure: 0.5 - 3.1 bar / 45 PSI
- Pressure Loss

Max.	0.4 Bar / 6 PSI. Measured at:
Flow:	10 l/min
Inlet:	2.4 Bar / 35 PSI 3.8 Bar / 55 PSI
Outlet:	1.0 Bar / 15 PSI 2.4 Bar / 35 PSI



FEATURES AND BENEFITS

- Compact design
- High capacity
- Easy to handle
- Balanced regulator
- Pull-adjust-lock movement secures the set pressure
- Integrated wall bracket and shut-off valve (SOV)
- Separate tamper evident device available

